

Automatic Exhaust Ceiling Shutter

16 to 50 inches

Please specify size when ordering.

FEATURES:

FRAME IS .062 EXTRUDED ALUMINUM WITH A POLAR WHITE ENAMEL FINISH.

(Also available in mill finish)

- Mounting flange is 1 $\frac{5}{16}$ "
- Ample number of mounting holes ($\frac{3}{16}$ " dia.)
- Can also be vertically mounted.

BLADES ARE 26 GAUGE ALUMINUM WITH A POLAR WHITE ENAMEL FINISH, WITH A GALVANIZED REINFORCEMENT STRIP.

(Also available in mill finish)

- Felt seal on leading edge for quiet operation.
- Brass bushings at all pivot points.
- Blades are spring counter balanced for easy opening and quiet closing.
- Can be motorized using model 904 MP motor pack kit.
- Flush mounting for clean appearance.
- Easy to install.



Front view

THIS SHUTTER IS FOR EXHAUST ONLY

- Maximum recommended velocity is 1500 F.P.M.
- Recommended distance for mounting ceiling shutter from the fan is $\frac{1}{3}$ the diameter of the fan.
- Shutters are individually packed.



Rear view with motor



Rear view without motor

ACP
co.
AIR CONDITIONING PRODUCTS CO.
SHUTTERS DAMPERS LOUVERS

30350 Ecorse Road • Romulus, MI 48174
Phone: 734/326-0050 • Fax: 734/326-9632